

PRICE LIST : SEPTEMBER 2017

LP NO. KEI/W&F/LP/17-18/04 DT. 02.09.2017

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	9	780	28	1560	12	8.67
1.00	32/0.20	14	1000	24	2000	12	11.11
1.50	30/0.25	18	1480	16	2960	8	16.44
2.50	50/0.25	24	2380	12	4760	6	26.44
4.00	56/0.30	32	3520	8	7040	4	39.11
6.00	84/0.30	42	5340	6	10680	3	59.33

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	9	820	28	1640	12	9.11
1.00	32/0.20	14	1060	24	2120	12	11.78
1.50	30/0.25	18	1560	16	3120	8	17.33
2.50	50/0.25	24	2510	12	5020	6	27.89
4.00	56/0.30	32	3700	8	7400	4	41.11
6.00	84/0.30	42	5550	6	11100	3	61.67

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	9	860	28	1720	12	9.56
1.00	32/0.20	14	1120	24	2240	12	12.44
1.50	30/0.25	18	1630	16	3260	8	18.11
2.50	50/0.25	24	2600	12	5200	6	28.89
4.00	56/0.30	32	3780	8	7560	4	42.00
6.00	84/0.30	42	5690	6	11380	3	63.22

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.